



MBR6040ST SERIES

SCHOTTKY BARRIER RECTIFIERS

VOLTAGE 40 to 100 Volts **CURRENT** 60 Amperes

FEATURES


- Plastic package has Underwriters Laboratory Flammability Classification 94V-O.
- Flame Retardant Epoxy Molding Compound.
- Metal silicon junction, majority carrier conduction
- Low power loss, high efficiency.
- High current capability
- Guardring for overvoltage protection
- For use in low voltage, high frequency inverters free wheeling, and polarity protection applications.
- In compliance with EU RoHS 2002/95/EC directives

MECHANICAL DATA

- Case: TO-247S / TO-3PS molded plastic
- Terminals: solder plated, solderable per MIL-STD-750, Method 2026
- Polarity: As marked.
- Mounting Position: Any
- Weight: 0.1932 ounces, 5.4803 grams.

TO-247S / TO-3PS

Unit : inch(mm)



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

PARAMETER	SYMBOL	MBR6040ST	MBR6045ST	MBR6080ST	MBR6090ST	MBR60100ST	UNITS
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	40	45	80	90	100	V
Maximum RMS Voltage	V_{RMS}	28	31.5	56	63	70	V
Maximum DC Blocking Voltage	V_{DC}	40	45	80	90	100	V
Maximum Average Forward Current	$I_{F(AV)}$			60			A
Peak Forward Surge Current : 8.3ms single half sine-wave superimposed on rated load (JEDEC method)	I_{FSM}			400			A
Maximum Forward Voltage at 30A per leg	V_F		0.7		0.8		V
Maximum DC Reverse Current at $T_J=25^{\circ}\text{C}$ Rated DC Blocking Voltage	I_R			0.1 20		0.05 20	mA
Typical Thermal Resistance	$R_{\theta JC}$			1.5			$^{\circ}\text{C} / \text{W}$
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55 to +150		-65 to +175			$^{\circ}\text{C}$

Note :

Both Bonding and Chip structure are available.



MBR6040ST SERIES

RATING AND CHARACTERISTIC CURVES




Fig.1- FORWARD CURRENT DERATING CURVE




Fig.2- MAXIMUM NON-REPETITIVE SURGE CURRENT




Fig.3- TYPICAL REVERSE CHARACTERISTIC




Fig.4- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTIC