

# GSM8803

## 20V P-Channel Enhancement Mode MOSFET

### Product Description

GSM8803, P-Channel enhancement mode MOSFET, uses Advanced Trench Technology to provide excellent  $R_{DS(ON)}$ , low gate charge.

These devices are particularly suited for low voltage power management, and low in-line power loss are needed in commercial industrial surface mount applications.


### Features

- -20V/-5.4A,  $R_{DS(ON)}=32m\Omega@V_{GS}=-4.5V$
- -20V/-4.0A,  $R_{DS(ON)}=42m\Omega@V_{GS}=-2.5V$
- -20V/-3.0A,  $R_{DS(ON)}=58m\Omega@V_{GS}=-1.8V$
- Super high density cell design for extremely low  $R_{DS(ON)}$
- TSSOP-8P package design


### Applications

- Load Switch
- Portable Equipment
- Battery Powered System

### Packages & Pin Assignments




## Ordering Information



Part Number	Package	Quantity Reel
GSM8803TSSF	TSSOP-8P	3000 PCS

## Marking Information



## Absolute Maximum Ratings

(T<sub>A</sub>=25°C unless otherwise noted)







Symbol	Parameter	Typical	Unit
V <sub>DSS</sub>	Drain-Source Voltage	-20	V
V <sub>GSS</sub>	Gate -Source Voltage	±12	V
I <sub>D</sub>	Continuous Drain Current(T <sub>J</sub> =150°C)	T <sub>A</sub> =25°C	-4.8
		T <sub>A</sub> =70°C	-3.0
I <sub>DM</sub>	Pulsed Drain Current	-20	A
I <sub>S</sub>	Continuous Source Current(Diode Conduction)	-1.5	A
P <sub>D</sub>	Power Dissipation	T <sub>A</sub> =25°C	2.8
		T <sub>A</sub> =70°C	1.8
T <sub>J</sub>	Operating Junction Temperature	150	°C
T <sub>STG</sub>	Storage Temperature Range	-55/150	°C
R <sub>θJA</sub>	Thermal Resistance-Junction to Ambient	62.5	°C/W

## Electrical Characteristics






( $T_A=25^{\circ}\text{C}$  unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
<b>Static</b>						
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=-250\mu A$	-20			V
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=-250\mu A$	-0.4		-0.9	
$I_{GSS}$	Gate Leakage Current	$V_{DS}=0V, V_{GS}=\pm 12V$			$\pm 100$	nA
$I_{DSS}$	Zero Gate Voltage Drain Current	$V_{DS}=-16V, V_{GS}=0V$			-1	uA
		$V_{DS}=-16V, V_{GS}=0V$ $T_J=85^{\circ}\text{C}$			-10	
$I_{D(on)}$	On-State Drain Current	$V_{DS}\leq -5V, V_{GS}=-4.5V$	-6			A
		$V_{DS}\leq -5V, V_{GS}=-2.5V$	-4			
$R_{DS(on)}$	Drain-Source On-Resistance	$V_{GS}=-4.5V, I_D=-5.4A$		23	32	m $\Omega$
		$V_{GS}=-2.5V, I_D=-4.0A$		30	42	
		$V_{GS}=-1.8V, I_D=-3.0A$		40	58	
$g_{FS}$	Forward Transconductance	$V_{DS}=-5V, I_D=-3.6A$		10		S
$V_{SD}$	Diode Forward Voltage	$I_S=-1.6A, V_{GS}=0V$		-0.85	-1.2	V
<b>Dynamic</b>						
$Q_g$	Total Gate Charge	$V_{DS}=-10V, V_{GS}=-4.5V$ $I_D=-4.0A$		15	25	nC
$Q_{gs}$	Gate-Source Charge			2.5		
$Q_{gd}$	Gate-Drain Charge			3.5		
$C_{iss}$	Input Capacitance	$V_{DS}=-10V, V_{GS}=0V$ $f=1\text{MHz}$		1050		pF
$C_{oss}$	Output Capacitance			165		
$C_{rss}$	Reverse Transfer Capacitance			125		
$t_{d(on)}$	Turn-On Time	$V_{DD}=-10V, R_L=10\Omega$ $I_D=-2.0A, V_{GEN}=-4.5V$ $R_G=6\Omega$		35	55	ns
$t_r$				60	85	
$t_{d(off)}$	Turn-Off Time			120	180	
$t_f$				55	85	

## Typical Performance Characteristics





## Typical Performance Characteristics (continue)





## Typical Characteristics



### Gate Charge Test Circuit & Waveform



### Resistive Switching Test Circuit & Waveforms




### Diode Recovery Test Circuit & Waveforms



Package Dimension

# TSSOP-8P PLASTIC PACKAGE







Dimensions				
SYMBOL	Millimeters		Inches	
	MIN	MAX	MIN	MAX
<b>D</b>	2.900	3.100	0.114	0.122
<b>E</b>	4.300	4.500	0.169	0.177
<b>b</b>	0.190	0.300	0.007	0.012
<b>c</b>	0.090	0.200	0.004	0.008
<b>E1</b>	6.250	6.550	0.246	0.258
<b>A</b>	-	1.100	-	0.043
<b>A2</b>	0.800	1.000	0.031	0.039
<b>A1</b>	0.020	0.150	0.001	0.006
<b>e</b>	0.65 BSC		0.026 BSC	
<b>L</b>	0.500	0.700	0.020	0.028
<b>H</b>	0.25 TYP		0.01 TYP	
<b>θ</b>	1°	7°	1°	7°





## NOTICE

Information furnished is believed to be accurate and reliable. However Globaltech Semiconductor assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Globaltech Semiconductor. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information without express written approval of Globaltech Semiconductor.



## CONTACT US

GS Headquarter	
	4F.,No.43-1,Lane11,Sec.6,Minquan E.Rd Neihu District Taipei City 114, Taiwan (R.O.C)
	886-2-2657-9980
	886-2-2657-3630
	sales_twn@gs-power.com

Wu-Xi Branch	
	No.21 Changjiang Rd., WND, Wuxi, Jiangsu, China (INFO. &. TECH. Science Park Building A 210 Room)
	86-510-85217051
	86-510-85211238
	sales_cn@gs-power.com

RD Division	
	824 Bolton Drive Milpitas. CA. 95035
	1-408-457-0587