

GSM4637W

40V P-Channel Enhancement Mode MOSFET

Product Description

GSM4637W, P-Channel enhancement mode MOSFET, uses Advanced Trench Technology to provide excellent $R_{DS(ON)}$, low gate charge.

These devices are particularly suited for low voltage power management, and low in-line power loss are needed in commercial industrial surface mount applications.


Features

- -40V/-6.8A, $R_{DS(ON)}=37m\Omega@V_{GS}=-10V$
- -40V/-5.8A, $R_{DS(ON)}=54m\Omega@V_{GS}=-4.5V$
- Super high density cell design for extremely low $R_{DS(ON)}$
- SOP-8P package design


Applications

- Backlight Inverter for LCD Display
- Full Bridge DC/DC Converter
- Load Switch
- CCFL Inverter

Packages & Pin Assignments




Ordering Information



Part Number	Package	Quantity Reel
GSM4637WSF	SOP-8P	2500 PCS

Marking Information



Absolute Maximum Ratings

$T_A=25^{\circ}\text{C}$ unless otherwise noted


Symbol	Parameter	Typical	Unit
V_{DSS}	Drain-Source Voltage	-40	V
V_{GSS}	Gate -Source Voltage	± 20	V
I_D	Continuous Drain Current ($T_J=150^{\circ}\text{C}$)	$T_A=25^{\circ}\text{C}$	-6.8
		$T_A=70^{\circ}\text{C}$	-5.8
I_{DM}	Pulsed Drain Current	-20	A
I_S	Continuous Source-Drain Diode Current	-2	
P_D	Power Dissipation	$T_A=25^{\circ}\text{C}$	2.8
		$T_A=70^{\circ}\text{C}$	1.8
T_J	Operating Junction Temperature	150	$^{\circ}\text{C}$
T_{STG}	Storage Temperature Range	-55/150	$^{\circ}\text{C}$
$R_{\theta JA}$	Thermal Resistance-Junction to Ambient	62.5	$^{\circ}\text{C}/\text{W}$

Electrical Characteristics


T_A=25°C unless otherwise noted

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static						
V _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =-250μA	-40			V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =-250μA	-1.5		-3.0	V
I _{GSS}	Gate Leakage Current	V _{DS} =0V, V _{GS} =±20V			±100	nA
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =-40V, V _{GS} =0V			-1	μA
		V _{DS} =-40V, V _{GS} =0V, T _J =85°C			-20	
I _{D(on)}	On-State Drain Current	V _{DS} ≤ -5V, V _{GS} = -10V	-20			A
R _{DS(on)}	Drain-Source On-Resistance	V _{GS} = -10V, I _D = -6.8A		30	37	mΩ
		V _{GS} = -4.5V, I _D = -5.8A		44	54	
g _{fs}	Forward Transconductance	V _{DS} = -15V, I _D = -5A		20		S
V _{SD}	Diode Forward Voltage	I _S = -2A, V _{GS} = 0V		-0.8	-1.2	V
Dynamic						
C _{iss}	Input Capacitance	V _{DS} = -20V, V _{GS} = 0V, f = 1MHz		1100		pF
C _{oss}	Output Capacitance			145		
C _{rss}	Reverse Transfer Capacitance			115		
Q _g	Total Gate Charge	V _{DS} = -20V, V _{GS} = -4.5V, I _D = -5.0A		13	20	nC
Q _{gs}	Gate-Source Charge			4.5		
Q _{gd}	Gate-Drain Charge			6.5		
t _{d(on)}	Turn-On Time	V _{DD} = -20V, R _L = 4Ω, I _D = -5.0A, V _{GEN} = -4.5V, R _G = 1Ω		40	80	ns
t _r				55	100	
t _{d(off)}	Turn-Off Time			30	60	
t _F				12	20	


Typical Performance Characteristics




Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current



Capacitance









Gate Charge




On-Resistance vs. Junction Temperature


Typical Performance Characteristics (continue)




Typical Performance Characteristics (continue)




* $V_{GS} >$ minimum V_{GS} at which $r_{DS(on)}$ is specified
Safe Operating Area, Junction-to-Case




Current Derating*, Junction-to-Ambient



Current Derating*, Junction-to-Case





Power Derating*, Junction-to-Ambient





Normalized Thermal Transient Impedance, Junction-to-Case

Typical Performance Characteristics (continue)



Gate Charge Test Circuit & Waveform



Resistive Switching Test Circuit & Waveforms




Diode Recovery Test Circuit & Waveforms



Package Dimension

SOP-8P PLASTIC PACKAGE






Dimensions




Symbol	Millimeters			Inches		
	Min	Nom	Max	Min	Nom	Max
A	1.47	1.60	1.73	0.058	0.063	0.068
A1	0.10	-	0.25	0.004	-	0.010
A2	-	1.45	-	-	0.057	-
b	0.33	0.41	0.51	0.013	0.016	0.020
C	0.19	0.20	0.25	0.0075	0.008	0.0098
D	4.80	4.85	4.95	0.189	0.191	0.195
E	5.80	6.00	6.20	0.228	0.236	0.244
E1	3.80	3.90	4.00	0.150	0.154	0.157
e	-	1.27	-	-	0.050	-
L	0.38	0.71	1.27	0.015	0.028	0.050
Δy	-	-	0.076	-	-	0.003
θ	0°	-	8°	0°	-	8°


NOTICE

Information furnished is believed to be accurate and reliable. However Globaltech Semiconductor assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Globaltech Semiconductor. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information without express written approval of Globaltech Semiconductor.

CONTACT US

GS Headquarter	
	4F.,No.43-1,Lane11,Sec.6,Minquan E.Rd Neihu District Taipei City 114, Taiwan (R.O.C)
	886-2-2657-9980
	886-2-2657-3630
	sales_twn@gs-power.com

Wu-Xi Branch	
	No.21 Changjiang Rd., WND, Wuxi, Jiangsu, China (INFO. &. TECH. Science Park Building A 210 Room)
	86-510-85217051
	86-510-85211238
	sales_cn@gs-power.com

RD Division	
	824 Bolton Drive Milpitas. CA. 95035
	1-408-457-0587