

GSM3484

30V N-Channel Enhancement Mode MOSFET

Product Description

GSM3484, N-Channel enhancement mode MOSFET, uses Advanced Trench Technology to provide excellent $R_{DS(ON)}$, low gate charge. These devices are particularly suited for low voltage power management, and low in-line power loss are needed in commercial industrial surface mount applications.


Features

- 30V/12A, $R_{DS(ON)}=15m\Omega@V_{GS}=10V$
- 30V/10A, $R_{DS(ON)}=18m\Omega@V_{GS}=4.5V$
- Super high density cell design for extremely low $R_{DS(ON)}$
- TO-252-2L package design


Applications

- Power Management in Desktop Computer
- DC/DC Converter
- LCD Display inverter

Packages & Pin Assignments




Ordering Information



Part Number	Package	Quantity Reel
GSM3484DF	TO-252-2L	2500 PCS

Marking Information



Absolute Maximum Ratings

(T_A=25°C unless otherwise noted)







Symbol	Parameter	Typical	Unit
V _{DSS}	Drain-Source Voltage	30	V
V _{GSS}	Gate -Source Voltage	±12	V
I _D	Continuous Drain Current(T _J =150°C)	T _A =25°C	25
		T _A =70°C	12
I _{DM}	Pulsed Drain Current	40	A
I _S	Continuous Source Current(Diode Conduction)	9.0	A
P _D	Power Dissipation	T _A =25°C	40
		T _A =70°C	15
T _J	Operating Junction Temperature	150	°C
T _{STG}	Storage Temperature Range	-55/150	°C
R _{θJA}	Thermal Resistance-Junction to Ambient	62.5	°C/ W

Electrical Characteristics






(T_A=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min.	Typ	Max.	Unit
Static						
V _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250uA	30			V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250uA	0.8		1.8	
I _{GSS}	Gate Leakage Current	V _{DS} =0V, V _{GS} =±20V			±100	nA
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =30V, V _{GS} =0V			1	uA
		V _{DS} =30V, V _{GS} =0V, T _J =85°C			10	
I _{D(on)}	On-State Drain Current	V _{DS} ≥5V, V _{GS} =10V	15			A
R _{DS(on)}	Drain-Source On-Resistance	V _{GS} =10V, I _D =12A		12	15	mΩ
		V _{GS} =4.5V, I _D =10A		14	18	
g _{fs}	Forward Transconductance	V _{DS} =15V, I _D =10A		24		S
V _{SD}	Diode Forward Voltage	I _S =3.0A, V _{GS} =0V		0.8	1.3	V
Dynamic						
C _{iss}	Input Capacitance	V _{DS} =15V, V _{GS} =0V, f=1MHz		800		pF
C _{oss}	Output Capacitance			180		
C _{rss}	Reverse Transfer Capacitance			70		
Q _g	Total Gate Charge	V _{DS} =15V, V _{GS} =4.5V, I _D ≐10A		8	12	nC
Q _{gs}	Gate-Source Charge			2.0		
Q _{gd}	Gate-Drain Charge			2.3		
t _{d(on)}	Turn-On Time	V _{DD} =15V, R _L =1.5Ω, I _D ≐10A V _{GEN} =10V, R _G =1Ω		8	15	ns
T _r				8	15	
t _{d(off)}	Turn-Off Time			16	28	
T _f				8	16	

Typical Performance Characteristics




Typical Performance Characteristics (continue)




Typical Characteristics


Gate Charge Test Circuit & Waveform



Resistive Switching Test Circuit & Waveforms




Unclamped Inductive Switching Test Circuit & Waveforms



Package Dimension

TO-252-2L











Dimensions				
SYMBOL	Millimeters		Inches	
	MIN	MAX	MIN	MAX
A	2.200	2.400	0.087	0.094
A1	0.000	0.127	0.000	0.005
B	1.350	1.650	0.053	0.065
b	0.700	0.900	0.028	0.035
c	0.430	0.580	0.017	0.023
c1	0.430	0.580	0.017	0.023
D	6.350	6.650	0.250	0.262
D1	5.200	5.400	0.205	0.213
E	5.400	5.700	0.213	0.224
e	2.300 TYP		0.091 TYP	
e1	4.500	4.700	0.177	0.185
L	9.500	9.900	0.374	0.390
L1	2.550	2.900	0.100	0.114
L2	1.400	1.780	0.055	0.070
L3	0.600	0.900	0.024	0.035
V	3.800 REF		0.150 REF	



NOTICE

Information furnished is believed to be accurate and reliable. However Globaltech Semiconductor assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Globaltech Semiconductor. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information without express written approval of Globaltech Semiconductor.

CONTACT US

GS Headquarter	
	4F.,No.43-1,Lane11,Sec.6,Minquan E.Rd Neihu District Taipei City 114, Taiwan (R.O.C)
	886-2-2657-9980
	886-2-2657-3630
	sales_twn@gs-power.com

Wu-Xi Branch	
	No.21 Changjiang Rd., WND, Wuxi, Jiangsu, China (INFO. &. TECH. Science Park Building A 210 Room)
	86-510-85217051
	86-510-85211238
	sales_cn@gs-power.com

RD Division	
	824 Bolton Drive Milpitas. CA. 95035
	1-408-457-0587