

GSM9987

90V N-Channel Enhancement Mode MOSFET

Product Description

GSM9987, N-Channel enhancement mode MOSFET, uses Advanced Trench Technology to provide excellent $R_{DS(ON)}$, low gate charge. These devices are particularly suited for low voltage power management, and low in-line power loss are needed in commercial industrial surface mount applications.


Features

- 90V/15A, $R_{DS(ON)} = 75m\Omega @ V_{GS} = 10V$
- 90V/12A, $R_{DS(ON)} = 85m\Omega @ V_{GS} = 4.5V$
- Super high density cell design for extremely low $R_{DS(ON)}$
- TO-252-2L package design


Applications

- High Frequency Boost Converter
- LED Backlight for LCD TV

Packages & Pin Assignments




Ordering Information



Part Number	Package	Quantity Reel
GSM9987DF	TO-252-2L	2500 PCS

Marking Information



Absolute Maximum Ratings

($T_A=25^\circ\text{C}$ unless otherwise noted)


Symbol	Parameter	Typical	Unit	
V_{DSS}	Drain-Source Voltage	90	V	
V_{GSS}	Gate –Source Voltage	± 20	V	
I_D	Continuous Drain Current($T_J=150^\circ\text{C}$)	$T_A=25^\circ\text{C}$	15	A
		$T_A=70^\circ\text{C}$	8	
I_{DM}	Pulsed Drain Current	50	A	
I_S	Continuous Source Current(Diode Conduction)	8	A	
I_{AS}	Single Pulse Avalanche Current	10	A	
P_D	Power Dissipation	$T_A=25^\circ\text{C}$	40	W
		$T_A=70^\circ\text{C}$	15	
T_J	Operating Junction Temperature	150	$^\circ\text{C}$	
T_{STG}	Storage Temperature Range	-55/150	$^\circ\text{C}$	
$R_{\theta JA}$	Thermal Resistance-Junction to Ambient	62.5	$^\circ\text{C}/\text{W}$	

Electrical Characteristics


($T_A=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Conditions	Min.	Typ	Max.	Unit
Static						
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu A$	90			V
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	1.0		2.5	
I_{GSS}	Gate Leakage Current	$V_{DS}=0V, V_{GS}=\pm 20V$			± 100	nA
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS}=90V, V_{GS}=0V$			1	uA
		$V_{DS}=80V, V_{GS}=0V$ $T_J=85^\circ\text{C}$			5	
$I_{D(on)}$	On-State Drain Current	$V_{DS} \geq 5V, V_{GS}=4.5V$	15			A
$R_{DS(on)}$	Drain-Source On-Resistance	$V_{GS}=10V, I_D=15A$		63	75	m Ω
		$V_{GS}=4.5V, I_D=12A$		69	85	
g_{FS}	Forward Transconductance	$V_{DS}=15V, I_D=5.3A$		24		S
V_{SD}	Diode Forward Voltage	$I_S=2.0A, V_{GS}=0V$		0.8	1.2	V
Dynamic						
Q_g	Total Gate Charge	$V_{DS}=50V, V_{GS}=5V$ $I_D=6.0A$		10	15	nC
Q_{gs}	Gate-Source Charge			4.0		
Q_{gd}	Gate-Drain Charge			5.0		
C_{iss}	Input Capacitance	$V_{DS}=50V, V_{GS}=0V$ $f=1\text{MHz}$		550		pF
C_{oss}	Output Capacitance			80		
C_{rss}	Reverse Transfer Capacitance			50		
$t_{d(on)}$	Turn-On Time	$V_{DD}=50V, R_L=14.5\Omega$ $I_D=5.0A, V_{GEN}=10V$ $R_G=1.0\Omega$		10	20	ns
t_r				10	20	
$t_{d(off)}$	Turn-Off Time			15	25	
t_f				10	25	


Typical Performance Characteristics




Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current



Capacitance








Gate Charge




On-Resistance vs. Junction Temperature

Typical Performance Characteristics (continue)




Typical Characteristics


Gate Charge Test Circuit & Waveform



Resistive Switching Test Circuit & Waveforms




Unclamped Inductive Switching Test Circuit & Waveforms



Package Dimension

TO-252-2L PLASTIC PACKAGE



Dimensions				
SYMBOL	Millimeters		Inches	
	MIN	MAX	MIN	MAX
A	2.200	2.400	0.087	0.094
A1	0.000	0.127	0.000	0.005
B	1.350	1.650	0.053	0.065
b	0.500	0.700	0.020	0.028
b1	0.700	0.900	0.028	0.035
c	0.430	0.580	0.017	0.023
c1	0.430	0.580	0.017	0.023
D	6.350	6.650	0.250	0.262
D1	5.200	5.400	0.205	0.213
E	5.400	5.700	0.213	0.224
e	2.300 TYP		0.091 TYP	
e1	4.500	4.700	0.177	0.185
L	9.500	9.900	0.374	0.390
L1	2.550	2.900	0.100	0.114
L2	1.400	1.780	0.055	0.070
L3	0.600	0.900	0.024	0.035
V	3.800 REF		0.150 REF	

NOTICE

Information furnished is believed to be accurate and reliable. However Globaltech Semiconductor assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Globaltech Semiconductor. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information without express written approval of Globaltech Semiconductor.

CONTACT US

GS Headquarter	
	4F.,No.43-1,Lane11,Sec.6,Minquan E.Rd Neihu District Taipei City 114, Taiwan (R.O.C)
	886-2-2657-9980
	886-2-2657-3630
	sales_twn@gs-power.com

Wu-Xi Branch	
	No.21 Changjiang Rd., WND, Wuxi, Jiangsu, China (INFO. &. TECH. Science Park Building A 210 Room)
	86-510-85217051
	86-510-85211238
	sales_cn@gs-power.com

RD Division	
	824 Bolton Drive Milpitas. CA. 95035
	1-408-457-0587