

Micro Commercial Components



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939

MGR1601 THRU MGR1607

16 Amp Glass Passivated Silicon Rectifiers 50 to 1000 Volts

Features

- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix designates
- RoHS Compliant. See ordering information) Low forward voltage drop
- High current capability
- High reliability
- High surge current capability
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0 and MSL Rating 1

Maximum Ratings

- Mounting Torgue: 5 in-lbs Maximum Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C
- Typical Thermal Resistance: 2.0°C/W Junction to Ambient


MCC Part Number	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
MGR1601	50V	35V	50V
MGR1602	100V	70V	100V
MGR1603	200V	140V	200V
MGR1604	400V	280V	400V
MGR1605	600V	420V	600V
MGR1606	800V	560V	800V
MGR1607	1000V	700V	1000V

Electrical Characteristics @ 25°C Unless Otherwise Specified

Maximum Average Forward Current	I _{F(AV)}	16 A	T _C = 100°C
Peak Forward Surge Current	I _{FSM}	250A	8.3ms, half sine
Maximum Instantaneous Forward Voltage	V _F	1.1V	I _F =16A T _A =25°ℂ
Maximum DC Reverse Current At Rated DC Blocking Voltage	I _R	10μA 250μA	$T_A = 25^{\circ}C$ $T_A = 125^{\circ}C$
Typical Junction Capacitance	CJ	100pF	Measured at 1.0MHz, V _R =4.0V

Notes:1.High Temperature Solder Exemption Applied, see EU Directive Annex 7.

TO-220AC






DIMENSIONS					
	INCHES		ММ		
DIM	MIN	MAX	MIN	MAX	NOTE
Α	.560	.625	14.22	15.88	
В	.380	.420	9.65	10.67	
С	.100	.135	2.54	3.43	
D	.230	.270	5.84	6.86	
F		.250		6.35	
G	.500	.580	12.70	14.73	
Η	.190	.210	4.83	5.33	
	.020	.045	0.51	1.14	
J	.012	.025	0.30	0.64	
K	.139	.161	3.53	4.09	Ø
Ĺ	.140	.190	3.56	4.83	
М	.045	.055	1.14	1.40	
N	.080	.115	2.03	2.92	


www.mccsemi.com


1 of 3


MGR1601 thru MGR1607
















Ordering Information

Device	Packing
(Part Number)-BP	Bulk;1Kpcs/Box

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.