

Triacs
Silicon Bidirectional Thyristors

TRIACS
8 AMPERES RMS
600 VOLTS

FEATURES

- Blocking Voltage to 600 Volts
- All Diffused and Glass Passivated Junctions for Greater Parameter Uniformity and Stability
- Small, Rugged, Thermowatt Construction for Low Thermal Resistance, High Heat Dissipation and Durability
- Gate Triggering Guaranteed in Four Modes

MECHANICAL DATA

- Case: Molded plastic
- Weight: 0.07 ounces, 2.0 grams

TO-220AB

TO-220AB		
DIM.	MIN.	MAX.
A	14.22	15.88
B	9.65	10.67
C	2.54	3.43
D	5.84	6.86
E	8.26	9.28
F	-	6.35
G	12.70	14.73
H	2.29	2.79
I	0.51	1.14
J	0.40	0.67
K	3.53 \varnothing	4.09 \varnothing
L	3.56	4.83
M	1.14	1.40
N	2.03	2.92
O	1.17	1.37

All Dimensions in millimeter

PIN ASSIGNMENT	
1	Main Terminal 1
2	Main Terminal 2
3	Gate
4	Main Terminal 2

MAXIMUM RATINGS (T_J= 25°C unless otherwise noticed)

Rating	Symbol	Value	Unit
Peak Repetitive Off- State Voltage (1) (T _J = -40 to 110°C, Sine Wave, 50 to 60 Hz; Gate Open)	V _{DRM} , V _{RRM}	600	Volts
T8M50F600B			
On-State RMS Current (T _C = +80°C) Full Cycle Sine Wave 50 to 60 Hz	I _{T(RMS)}	8.0	Amp
Peak Non-Repetitive Surge Current (One Full Cycle Sine Wave, 60 Hz, T _J = +25°C)	I _{TSM}	100	Amps
Circuit Fusing Consideration (t = 8.3 ms)	I ² t	40	A ² s
Peak Gate Power (T _C = +80°C, T _p = 2.0us)	P _{GM}	20	Watt
Average Gate Power (T _C = +80°C, t=8.3 ms)	P _{G(AV)}	0.5	Watt
Peak Gate Current (T _C = +80°C, T _p =2.0 us)	I _{GM}	2.0	Amp
Peak Gate Voltage (T _C = +80°C, T _p =2.0 us)	V _{GM}	10	Volts
Operating Junction Temperature Range	T _J	-40 to +125	°C
Storage Temperature Range	T _{stg}	-40 to +150	°C

Notice: (1) V_{DRM} and V_{RRM} for all types can be applied on a continuous basis. Blocking voltages shall not be tested with a constant current source such that the voltage ratings of the devices are exceeded.

THERMAL CHARACTERISTICS

Characteristic	Symbol	Value	Unit
Thermal Resistance - Junction to Case	RthJC	2.2	°C/W
Maximum Lead Temperature for Soldering Purposes 1/8" from Case for 10 Seconds	TL	260	°C

ELECTRICAL CHARACTERISTICS (T_c=25°C unless otherwise noted, Electrical apply in both directions)

Characteristics	Symbol	Min	Typ	Max	Unit
-----------------	--------	-----	-----	-----	------

OFF CHARACTERISTICS

Peak Repetitive Forward or Reverse Blocking Current (V _D =Rated V _{DRM} , V _{RRM} ; Gate Open)	T _J =25°C	I _{DRM}	----	----	10	µA
	T _J =100°C	I _{RRM}	----	----	2.0	mA


ON CHARACTERISTICS

Peak On-State Voltage (I _{TM} =± 11A Peak @T _p =1 to 2 ms, Duty Cycle ≤ 2%)	V _{TM}	----	1.3	1.55	Volts
Gate Trigger Current (V _D = 12Vdc; R _L = 100 Ohms)	I _{GT1}	----	12	50	mA
	I _{GT2}	----	12	75	
	I _{GT3}	----	20	50	
	I _{GT4}	----	35	75	
Gate Trigger Voltage (V _D = 12 Vdc; R _L =100 Ohms)	V _{GT1}	----	0.9	2.0	Volts
	V _{GT2}	----	0.9	2.5	
	V _{GT3}	----	1.1	2.0	
	V _{GT4}	----	1.4	2.5	
Holding Current (V _D = 12 V, Initiating Current = ± 200 mA, Gate Open)	I _H	----	6.0	40	mA
Gate Non - Trigger Voltage (Main Terminal Voltage=12 V, R _L =10K Ohms, T _J =100°C) All Four Quadrants	V _{GD}	0.2	----	----	Volts
Turn-On Time (V _D = Rated V _{DRM} , I _{TM} = 11 A, I _{GT} = 120 mA) Rise Time=0.1 us, Pulse Windth= 2 us)	t _{gt}	----	1.5	2.0	us


DYNAMIC CHARACTERISTICS

Critical Rate of Rise of Commutation Voltage (V _D = Rated V _{DRM} , I _{TM} = 11 A, Commutating di/dt = 4.0 A/ms, Gate Unenergized, T _C = 80°C)	dv/dt(c)	----	5.0	----	V/us
--	----------	------	-----	------	------

Symbol	Parameter
V_{DRM}	Peak Repetitive Forward Off State Voltage
I_{DRM}	Peak Forward Blocking Current
V_{RRM}	Peak Repetitive Reverse Off State Voltage
I_{RRM}	Peak Reverse Blocking Current
V_{TM}	Maximum On State Voltage
I_H	Holding Current



Quadrant Definitions



All polarities are referenced to MT1

Whith in -phase signal (using standard AC lines) quadrants I and III are used




Figure 1. RMS Current Derating




Figure 2. On-State Power Dissipation




Figure 3. Typical Gate Trigger Voltage




Figure 4. Typical Gate Trigger Current




Figure 5. On-State Characteristics




Figure 6. Typical Holding Current




Figure 7. Maximum Non-Repetitive Surge Current




Figure 8. Typical Thermal Response

Important Notice and Disclaimer

LSC reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

LSC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does LSC assume any liability for application assistance or customer product design. LSC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of LSC.

LSC products are not authorized for use as critical components in life support devices or systems without express written approval of LSC.