



PRELIMINARY DATASHEET
**70A, 1600V Rectifier Diodes,
 In TO247 B1 version**

- Low forward voltage
- High surge capability
- 150 °C maximum junction temperature
- Pb-free lead finish; RoHS compliant


MAXIMUM RATINGS, at $T_j = 25^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Value	Units
Repetitive peak reverse voltage	V_{RRM}	1600	V
Maximum average forward current 180° conduction, half sine wave, $T_c = 110^\circ\text{C}$	$I_{F(AV)}$	70	A
Peak surge non-repetitive forward current $t_p = 10\text{ms}$, No voltage reapplied, Half wave sine	I_{FSM}	1300	
Operating junction and storage temperature	T_j, T_{stg}	-40... +150	

Thermal Characteristics

Parameter	Symbol	Max. Value	Units
Characteristics			
Thermal resistance, junction to case	R_{thJC}	0.29	$^\circ\text{C}/\text{W}$

Electrical Characteristics, at $T_j = 25^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Value			Unit
		Min.	Typ.	Max.	
Static Characteristics					
Reverse leakage current $V_R = 1600\text{V}$	I_R	-	-	10	mA
Forward voltage drop $I_F = 70\text{A}$	V_F	-	1.1	-	V

Package Outline Drawing

