


**PRELIMINARY DATASHEET**
**Fast Recovery, 75A, 600V Diodes  
In Isolated SOT227 Package**

- Fast recovery
- Soft switching
- Low forward voltage
- Easy paralleling
- Pb-free lead finish; RoHS compliant


**MAXIMUM RATINGS**, at  $T_j = 25^\circ\text{C}$ , unless otherwise specified

Parameter	Symbol	Value	Units
Repetitive peak reverse voltage	$V_{RRM}$	600	V
Continuous forward current $T_c = 25^\circ\text{C}$ $T_c = 77^\circ\text{C}$	$I_F$	100 75	A
Surge non-repetitive forward current $T_c = 25^\circ\text{C}$ , $t_p = 10 \text{ ms}$ , sine halfwave	$I_{FSM}$	220	
Maximum repetitive forward current $T_c = 25^\circ\text{C}$ , $t_p$ limited by $T_{jmax}$ , $D = 0.5$	$I_{FRM}$	225	
Soldering temperature Wave soldering, 1.6 mm (0.063 in.) from case for 10s	$T_s$	260	$^\circ\text{C}$
Operating junction and storage temperature	$T_j$ , $T_{stg}$	-55... +175	$^\circ\text{C}$

**Thermal and Isolation Characteristics**


Parameter	Symbol	Max. Value	Units
<b>Characteristics</b>			
Thermal resistance, junction to case	$R_{thJC}$	0.65	K/W
Thermal resistance, junction to ambient, leaded	$R_{thJA}$	40	
Isolation voltage, RMS (measured between terminals and mounting base, 50-60 Hz, for 1-3 seconds)	$V_{iso}$	3000	V

**Electrical Characteristics**, at  $T_j = 25^\circ\text{C}$ , unless otherwise specified

Parameter	Symbol	Value			Unit
		Min.	Typ.	Max.	
<b>Static Characteristics</b>					
Reverse leakage current $V_R = 600\text{V}$ , $T_j = 25^\circ\text{C}$ $V_R = 600\text{V}$ , $T_j = 175^\circ\text{C}$	$I_R$	- -	- -	40 1000	$\mu\text{A}$
Forward voltage drop $I_F = 75\text{A}$ , $T_j = 25^\circ\text{C}$ $I_F = 75\text{A}$ , $T_j = 175^\circ\text{C}$	$V_F$	- -	1.65 1.65	2.0 -	V

**Electrical Characteristics**, at  $T_j = 25^\circ\text{C}$ , unless otherwise specified

Parameter	Symbol	Value			Unit
		Min.	Typ.	Max.	
<b>Dynamic Characteristics</b>					
Reverse recovery time $V_R = 300V$ , $I_F = 75A$ , $dI_F/dt = 200A/\mu\text{s}$ , $T_j = 25^\circ\text{C}$ $V_R = 300V$ , $I_F = 75A$ , $dI_F/dt = 200A/\mu\text{s}$ , $T_j = 125^\circ\text{C}$	$t_{rr}$	-	264 548	-	ns
Peak reverse current $V_R = 300V$ , $I_F = 75A$ , $dI_F/dt = 200A/\mu\text{s}$ , $T_j = 25^\circ\text{C}$ $V_R = 300V$ , $I_F = 75A$ , $dI_F/dt = 200A/\mu\text{s}$ , $T_j = 125^\circ\text{C}$	$I_{rm}$	-	8.3 12.9	-	A
Reverse recovery charge $V_R = 300V$ , $I_F = 75A$ , $dI_F/dt = 200A/\mu\text{s}$ , $T_j = 25^\circ\text{C}$ $V_R = 300V$ , $I_F = 75A$ , $dI_F/dt = 200A/\mu\text{s}$ , $T_j = 125^\circ\text{C}$	$Q_{rr}$	-	908 2941	-	nC

**Package Outline Drawing**

**Disclaimer**

These specifications may not be considered as a guarantee of components characteristics. Components have to be tested depending on intended application as adjustments may be necessary. The use of **iQXPRZ Power Inc.** components in life support appliances and systems are subject to written approval of **iQXPRZ Power Inc.**