


## PRELIMINARY DATASHEET

### Parallel Fast Recovery, 4X30A, 1200V Diodes In Isolated SOT227 Package

#### APPLICATIONS

- Switch mode power supplies (SMPS) rectifiers
- Uninterruptible power supplies (UPS)
- Ultrasonic cleaners and welders
- Inductive heating and melting
- Ultrasonic cleaners and welders
- Power factor correction (PFC) circuits
- Inversion welder
- Converter and chopper



#### FEATURES

- Ultrafast recovery time
- Soft recovery characteristics
- Low recovery loss
- Low forward voltage
- High surge current capability
- Low leakage current
- Pb free finished; **RoHS compliant**



#### MAXIMUM RATINGS (per Leg)

Parameter	Symbol	Value	Units
Repetitive peak reverse voltage	$V_{RRM}$	1200	V
Continuous forward current $T_C = 80^\circ\text{C}$	$I_F$	60	A
Surge non-repetitive forward current $T_J = 45^\circ\text{C}$ , $t_p = 10$ ms, 50Hz, Sine	$I_{FSM}$	600	
Operating junction and storage temperature	$T_J, T_{stg}$	-40... +150	$^\circ\text{C}$

#### Thermal and Isolation Characteristics

Parameter	Symbol	Max. Value	Units
<b>Characteristics</b>			
Thermal resistance, junction to case, per Leg	$R_{thJC}$	0.7	$^\circ\text{C}/\text{W}$
Isolation voltage, RMS (measured between terminals and mounting base, 50-60 Hz, for 1- 3 seconds)	$V_{iso}$	3000	V

**Electrical Characteristics (per Leg), at  $T_j = 25^\circ\text{C}$ , unless otherwise specified**

Parameter	Symbol	Value			Unit
		Min.	Typ.	Max.	
<b>Static Characteristics</b>					
Reverse leakage current $V_R = 1200\text{ V}, T_j = 25^\circ\text{C}$ $V_R = 1200\text{ V}, T_j = 150^\circ\text{C}$	$I_R$	-	-	0.2 2.0	mA
Forward voltage drop $I_F = 60\text{ A}, T_j = 25^\circ\text{C}$ $I_F = 60\text{ A}, T_j = 150^\circ\text{C}$	$V_F$	-	2.0 1.5	2.5 -	V

**Electrical Characteristics (per Leg), at  $T_C = 25^\circ\text{C}$ , unless otherwise specified**

Parameter	Symbol	Value			Unit
		Min.	Typ.	Max.	
<b>Dynamic Characteristics</b>					
Reverse recovery time $V_R = 30\text{ V}, I_F = 1\text{ A}, di_F/dt = -200\text{ A}/\mu\text{s}$ $V_R = 600\text{ V}, I_F = 60\text{ A}, di_F/dt = -200\text{ A}/\mu\text{s}, T_C = 25^\circ\text{C}$ $V_R = 600\text{ V}, I_F = 60\text{ A}, di_F/dt = -200\text{ A}/\mu\text{s}, T_C = 150^\circ\text{C}$	$t_{rr}$	-	33 258 469	-	ns
Reverse recovery charge $V_R = 600\text{ V}, I_F = 60\text{ A}, di_F/dt = -200\text{ A}/\mu\text{s}, T_C = 25^\circ\text{C}$ $V_R = 600\text{ V}, I_F = 60\text{ A}, di_F/dt = -200\text{ A}/\mu\text{s}, T_C = 150^\circ\text{C}$	$Q_{rr}$	-	0.65 7.51	-	$\mu\text{C}$
Maximum reverse recovery current $V_R = 600\text{ V}, I_F = 60\text{ A}, di_F/dt = -200\text{ A}/\mu\text{s}, T_C = 25^\circ\text{C}$ $V_R = 600\text{ V}, I_F = 60\text{ A}, di_F/dt = -200\text{ A}/\mu\text{s}, T_C = 150^\circ\text{C}$	$I_{rm}$	-	7.05 23.5	-	A



**Figure 1 – Forward voltage drop vs forward current**

**Figure 2 – Reverse recovery time vs  $di_F/dt$** 


Figure 3 – Reverse recovery charge vs  $di_F/dt$




Figure 4 – Reverse recovery current vs  $di_F/dt$







Figure 5 – Diode Reverse Recovery Test Circuit and Waveform



**Package Outline Drawing**



**Disclaimer**

These specifications may not be considered as a guarantee of components characteristics. Components have to be tested depending on intended application as adjustments may be necessary. The use of **iQXPRZ Power Inc.** components in life support appliances and systems are subject to written approval of **iQXPRZ Power Inc.**