

## GLASS PASSIVATED BRIDGE RECTIFIERS


REVERSE VOLTAGE - 50 to 1000Volts  
FORWARD CURRENT - 4.0 Amperes

### FEATURES

- Glass passivated chip junction
  - High case dielectric strength
  - High surge current capability
- Ideal for printed circuit board

### MACHANICAL DATA

- Terminal: Plated leads solderable per MIL-STD 202E, Method 208C
- Case: UL-94 Class V-0 recognized Flame Retardant Epoxy
- Polarity: Polarity symbol marked on body
- Mounting position: any



Dimensions in inches and (millimeters)

### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%

CHARACTERISTICS	SYMBOL	D4KB05	D4KB1	D4KB2	D4KB4	D4KB6	D4KB8	D4KB10	UNIT
Maximum Recurrent Peak Reverse Voltage	V <sub>RRM</sub>	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V <sub>RMS</sub>	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V <sub>DC</sub>	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Output Current @ T <sub>c</sub> =138°C (with heatsink)	I <sub>(AV)</sub>	4							A
Peak Forward Surge Current 8.3ms Single Half Sine-Wave Super Imposed on Rated Load (JEDEC Method)	I <sub>FSM</sub>	135							A
Maximum Forward Voltage at 2.0A DC	V <sub>F</sub>	1.0							V
Maximum Forward Voltage at 4.0A DC	V <sub>F</sub>	1.1							V
I <sup>2</sup> t Rating for Fusing (t<8.3ms)	I <sup>2</sup> t	64.84							A <sup>2</sup> s
Typical Thermal Resistance	without heatsink	R <sub>θJa</sub>							°C/W
	with heatsink	R <sub>θJC</sub>							
	without heatsink	R <sub>θJL</sub>							
Maximum DC Reverse Current at Rated DC Blocking Voltage	@ T <sub>a</sub> =25°C	I <sub>R</sub>							μA
	@ T <sub>a</sub> =125°C	10.0							
Operating Temperature Range	T <sub>J</sub>	-55 to +150							°C
Storage Temperature Range	T <sub>STG</sub>	-55 to +150							°C

FIG.1-DERATING CURVE OUTPUT RECTIFIED CURRENT




FIG.2-MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3-TYPICAL JUNCTION CAPACITANCE




FIG.3-TYPICAL FORWARD CHARACTERISTICS




FIG.5-TYPICAL REVERSE CHARACTERISTICS

