


**GLASS PASSIVATED  
3 PHASE BRIDGE RECTIFIERS**

REVERSE VOLTAGE - 800Volts  
FORWARD CURRENT - 35Amperes

**FEATURES**

- Surge overload -350 amperes peak
- Low forward voltage drop
- Mounting position :Any
- Weight: 45g

**SCVB**



Dimensions in inches and (milimeters)

**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

Rating at 25°C ambient temperature unless otherwise specified.

Resistive or inductive load 60Hz.

For capacitive load, derate current by 20%

CHARACTERISTICS	SYMBOL	SC35VB80	UNIT
Maximum Recurrent Peak Reverse Voltage	V <sub>RRM</sub>	800	V
Maximum RMS Bridge Input Voltage	V <sub>RMS</sub>	560	V
Maximum Average Forward Rectified Output Current @ T <sub>C</sub> =55°C	I <sub>(AV)</sub>	35	A
Peak Forward Surge Current 8.3ms Single Half Sine-Wave Super Imposed on Rated Load	I <sub>FSM</sub>	350	A
Current Squared time (1ms<t<10ms)	I <sup>2</sup> t	300	A <sup>2</sup> S
Dielectric Strength	V <sub>dis</sub>	2000	V
Mounting Torque	T <sub>OR</sub>	0.8	N.m
Maximum Forward Voltage Drop Per Element at 12.5 A Peak	V <sub>F</sub>	1.05	V
Maximum Reverse Current at Rated DC Blocking Voltage Per Element @ T <sub>A</sub> =25°C	I <sub>R</sub>	10	μA
Typical Thermal Resistance (Note1)	R <sub>θJC</sub>	Max: 0.7	°C/W
Operating Temperature Range	T <sub>J</sub>	-55 to +150	°C
Storage Temperature Range	T <sub>STG</sub>	-55 to +150	°C

NOTES: 1. Thermal Resistance Junction to case.

FIG.1-MAXMUN FORWARD SURGE CURRENT




FIG.2- DERATING CURVE OUTPUT RECTIFIED CURRENT




FIG.3-TYPICAL FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS

