

# OR-ing Power Schottky Rectifier


## Non isolated

$$I_{FAVM} = 2x200 \text{ A}$$


$$V_{RRM} = 8 \text{ V}$$

$$V_F = 0.15 \text{ V}$$

$V_{RSM}$	$V_{RRM}$	Type
V	V	
8	8	DSS 2x200-0008D



miniBLOC, SOT-227 B



Common cathode

Symbol	Conditions	Maximum Ratings	
$I_{FRMS}$		200	A
$I_{FAVM}$	$T_C = 100^\circ\text{C}$ ; rectangular, $d = 0.5$	200	A
$I_{FAVM}$	$T_C = 100^\circ\text{C}$ ; rectangular, $d = 0.5$ ; per device	400	A
$I_{FSM}$	$T_{VJ} = 45^\circ\text{C}$ ; $t_p = 10 \text{ ms}$ (50 Hz), sine	1600	A
$E_{AS}$	$I_{AS} = \text{tbd}$ ; $L = 180 \mu\text{H}$ ; $T_{VJ} = 25^\circ\text{C}$ ; non repetitive	tbd	mJ
$I_{AR}$	$V_A = 1.5 \cdot V_{RRM}$ typ.; $f = 10 \text{ kHz}$ ; repetitive	tbd	A
$(dv/dt)_{cr}$		5000	V/ $\mu\text{s}$
$T_{VJ}$		-40...+150	$^\circ\text{C}$
$T_{VJM}$		150	$^\circ\text{C}$
$T_{stg}$		-40...+150	$^\circ\text{C}$
$P_{tot}$	$T_C = 25^\circ\text{C}$	310	W
$M_d$	mounting torque (M4)	1.1-1.5/9-13	Nm/lb.in.
	terminal connection torque (M4)	1.1-1.5/9-13	Nm/lb.in.
Weight	typical	30	g

### Features

- International standard package miniBLOC
- Epoxy meets UL 94V-0
- Very low  $V_F$
- Extremely low switching losses
- Low  $I_{RM}$ -values

### Applications

- Rectifiers in switch mode power supplies (SMPS)
- Free wheeling diode in low voltage converters

### Advantages

- High reliability circuit operation
- Low voltage peaks for reduced protection circuits
- Low noise switching
- Low losses

Dimensions see IXYS Data Book 2001 pages D2 - 87-88

Symbol	Conditions	Characteristic Values	
		typ.	max.
$I_R$ ①	$T_{VJ} = 25^\circ\text{C}$ ; $V_R = V_{RRM}$		400 mA
	$T_{VJ} = 100^\circ\text{C}$ ; $V_R = V_{RRM}$		3000 mA
$V_F$	$I_F = 100 \text{ A}$ ; $T_{VJ} = 125^\circ\text{C}$		0.23 V
	$T_{VJ} = 25^\circ\text{C}$		0.34 V
	$I_F = 200 \text{ A}$ ; $T_{VJ} = 125^\circ\text{C}$		0.34 V
	$I_F = 100 \text{ A}$ ; $T_{VJ} = 150^\circ\text{C}$ ; per device		0.15 V
$R_{thJC}$		0.4	K/W
$R_{thCH}$	0.15		K/W

Pulse test: ① Pulse Width = 5 ms, Duty Cycle < 2.0 %  
Data according to IEC 60747 and per diode unless otherwise specified

IXYS reserves the right to change limits, Conditions and dimensions.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[IXYS:](#)

[DSS2x200-0008D](#)