


# Rectifier Diode

with common cathode


$V_{RRM} = 1600\text{ V}$   
 $I_{F(AV)M} = 45\text{ A}$

Preliminary data sheet

$V_{RSM}$ V	$V_{RRM}$ V	Type
1700	1600	DSIK 45-16AR



ISOPLUS 247™



A = Anode, C = Cathode

Symbol	Conditions	Maximum Ratings	
$I_{F(AV)M}$	$T_C = 100^\circ\text{C}$ ; 180° sine	45	A
$I_{FSM}$	$T_{VJ} = 45^\circ\text{C}$ ; $t = 10\text{ ms}$ (50 Hz), sine	475	A
	$V_R = 0\text{ V}$ ; $t = 8.3\text{ ms}$ (60 Hz), sine	510	A
$I^2t$	$T_{VJ} = 150^\circ\text{C}$ ; $t = 10\text{ ms}$ (50 Hz), sine	410	A
	$V_R = 0\text{ V}$ ; $t = 8.3\text{ ms}$ (60 Hz), sine	440	A
$T_{VJ}$	$T_{VJ} = 45^\circ\text{C}$ ; $t = 10\text{ ms}$ (50 Hz), sine	1130	A <sup>2</sup> s
	$V_R = 0\text{ V}$ ; $t = 8.3\text{ ms}$ (60 Hz), sine	1090	A <sup>2</sup> s
$T_{VJM}$	$T_{VJ} = 150^\circ\text{C}$ ; $t = 10\text{ ms}$ (50 Hz), sine	840	A <sup>2</sup> s
	$V_R = 0\text{ V}$ ; $t = 8.3\text{ ms}$ (60 Hz), sine	810	A <sup>2</sup> s
$T_{stg}$		-40...+150	°C
		150	°C
		-40...+150	°C
$F_C$	mounting force with clips	20...120	N
$V_{ISOL}$	50/60 Hz, RMS, $t = 1\text{ minute}$ , leads-to-tab	2500	V~
Weight	typical	6	g

## Features

- International standard package
- Planar glassivated chips
- Isolated and UL registered E153432
- Epoxy meets UL 94V-0


## Applications

- Supplies for DC power equipment
- DC supply for PWM inverter
- Field supply for DC motors
- Battery DC power supplies

## Advantages

- Space and weight savings
- Simple mounting
- Improved temperature and power cycling
- Reduced protection circuits

## ISOPLUS247™ OUTLINE



DIM.	MILLIMETER		INCHES	
	MIN	MAX	MIN	MAX
A	4,83	5,21	0,190	0,205
A1	2,29	2,54	0,090	0,100
A2	1,91	2,16	0,075	0,085
b	1,14	1,40	0,045	0,055
b1	1,91	2,15	0,075	0,085
b2	2,92	3,20	0,115	0,126
C	0,61	0,83	0,024	0,033
D	20,80	21,34	0,819	0,840
E	15,75	16,13	0,620	0,635
e	5,45 BSC		0,215 BSC	
L	19,81	20,60	0,780	0,811
L1	3,81	4,38	0,150	0,172
Q	5,59	6,20	0,220	0,244
R	4,32	4,85	0,170	0,191
S	13,21	13,72	0,520	0,540
T	15,75	16,26	0,620	0,640
U	1,65	2,03	0,065	0,080
W	-	0,10	-	0,004

The convex bow of substrate is typ. < 0.04 mm over plastic surface level of device bottom side  
 This drawing will meet all dimensions requirement of JEDEC outline TO-247 AD except screw hole and except Lmax.

Symbol	Conditions	Characteristic Values	
$I_R$	$T_{VJ} = T_{VJM}$ ; $V_R = V_{RRM}$	≤ 3	mA
$V_F$	$I_F = 40\text{ A}$ ; $T_{VJ} = 25^\circ\text{C}$	≤ 1.22	V
$V_{T0}$	For power-loss calculations only	0.8	V
$r_T$	$T_{VJ} = T_{VJM}$	8	mΩ
$R_{thJC}$	DC current	0.65	K/W
$R_{thCH}$	typical	0.2	K/W

Data according to IEC 60747  
 IXYS reserves the right to change limits, test conditions and dimensions.