

SCHOTTKY BARRIER RECTIFIER

VOLTAGE RANGE: 60 V
CURRENT: 3.0 A


FEATURES

- ◇ Metal-Semiconductor junction with guard ring
- ◇ Epitaxial construction
- ◇ Low forward voltage drop, low switching losses
- ◇ High surge capability
- ◇ For use in low voltage, high frequency inverters free wheeling, and polarity protection applications
- ◇ The plastic material carries U/L recognition 94V-0

MECHANICAL DATA

- ◇ Case: JEDEC DO--27, molded plastic
- ◇ Terminals: Axial lead, solderable per MIL-STD-202, Method 208
- ◇ Polarity: Color band denotes cathode
- ◇ Weight: 0.041 unces, 1.15 grams
- ◇ Mounting position: Any

DO - 27



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 50 Hz, resistive or inductive load. For capacitive load, derate by 20%.

		SR360P	UNITS
Maximum recurrent peak reverse voltage	V_{RRM}	60	V
Non repetitive peak reverse voltage	V_{RSM}	65	V
Maximum average forward rectified current 9.5mm lead length	$I_{F(AV)}$	3.0	A
Peak forward surge current 10ms single half-sine-wave superimposed on rated load	I_{FSM}	80	A
Maximum instantaneous forward voltage @ 3.0A (Note1)	V_F	0.58	V
Maximum reverse current at rated DC blocking voltage @ $T_J=25^\circ\text{C}$	I_R	2.5	mA
Typical thermal resistance	$R_{\theta JA}$	62	$^\circ\text{C}/\text{W}$
Operating junction temperature range	T_J	- 55 ---- + 150	$^\circ\text{C}$
Storage temperature range	T_{STG}	- 55 ---- + 150	$^\circ\text{C}$

Note: 1. Pulse test : 300 μ s pulse width, 1% duty cycle.

www.galaxycn.com

FIG.1 – TYPICAL FORWARD CHARACTERISTIC




FIG.2- FORWARD DERATING CURVE




FIG.3- PEAK FORWARD SURGE CURRENT

